


Metric Tube end as per ISO 8434



\*

| Part No.      | Series                    | Tube od | ød8 | I 1  | L1   | S1 | S2 |
|---------------|---------------------------|---------|-----|------|------|----|----|
| <b>AS06PL</b> | <b>Light L</b><br>250 bar | 6       | 10  | 14.0 | 29.5 | 12 | 14 |
| <b>AS08PL</b> |                           | 8       | 12  | 16.0 | 31.0 | 14 | 17 |
| <b>AS10PL</b> |                           | 10      | 14  | 18.0 | 33.5 | 17 | 19 |
| <b>AS12PL</b> |                           | 12      | 16  | 18.0 | 33.0 | 19 | 22 |
| <b>AS15PL</b> |                           | 15      | 19  | 22.0 | 38.0 | 22 | 27 |
| <b>AS18PL</b> | 160 bar                   | 18      | 22  | 23.5 | 40.5 | 27 | 32 |
| <b>AS22PL</b> |                           | 22      | 27  | 28.5 | 45.5 | 32 | 36 |
| <b>AS28PL</b> | 100 bar                   | 28      | 32  | 30.5 | 48.5 | 41 | 41 |
| <b>AS35PL</b> |                           | 35      | 40  | 32.5 | 55.5 | 46 | 50 |
| <b>AS42PL</b> |                           | 42      | 46  | 35.0 | 58.5 | 55 | 60 |
| <b>AS06PS</b> | <b>Heavy S</b><br>630 bar | 6       | 11  | 19.0 | 34.5 | 14 | 17 |
| <b>AS08PS</b> |                           | 8       | 13  | 21.0 | 36.0 | 17 | 19 |
| <b>AS10PS</b> |                           | 10      | 15  | 22.5 | 39.5 | 19 | 22 |
| <b>AS12PS</b> |                           | 12      | 17  | 24.5 | 41.0 | 22 | 24 |
| <b>AS16PS</b> | 400 bar                   | 16      | 21  | 26.5 | 45.5 | 27 | 30 |
| <b>AS20PS</b> |                           | 20      | 26  | 29.5 | 52.0 | 32 | 36 |
| <b>AS25PS</b> |                           | 25      | 31  | 32.0 | 57.0 | 41 | 46 |
| <b>AS30PS</b> | 250 bar                   | 30      | 36  | 35.5 | 63.5 | 46 | 50 |
| <b>AS38PS</b> |                           | 38      | 44  | 38.0 | 69.5 | 55 | 60 |

\* Dimensions given are approx figures with tightened nut.