


Socket head Plug with O-Ring (ISO 6149-4)
Male thread : Metric (M) - ISO 261



Part No.	Working Pressure (bar)	M Male thread Metric	Ød3	i	L2	S6	O-Ring ID x CSD	Tightening Torque N-m
VSTIM100	420	M10 x 1.0	13.8	9.5	13.5	5	8.1 x 1.6	15
VSTIM120	420	M12 x 1.5	16.8	11.0	15.5	6	9.3 x 2.2	22
VSTIM140	630	M14 x 1.5	18.8	11.0	16.0	6	11.3 x 2.2	45
VSTIM160	630	M16 x 1.5	21.8	12.5	17.5	8	13.3 x 2.2	55
VSTIM180	630	M18 x 1.5	23.8	14.0	19.0	8	15.3 x 2.2	70
VSTIM220	630	M22 x 1.5	26.8	15.0	20.0	10	19.3 x 2.2	100
VSTIM260	* 400	M26 x 1.5	31.0	16.0	21.0	12	23.0 x 2.4	---
VSTIM270	400	M27 x 2.0	31.8	18.5	23.5	12	23.6 x 2.9	170
VSTIM300	400	M30 x 2.0	35.8	18.5	24.5	14	26.6 x 2.9	215
VSTIM330	400	M33 x 2.0	40.8	18.5	24.5	14	29.6 x 2.9	310
VSTIM420	250	M42 x 2.0	49.8	19.0	25.0	17	38.6 x 2.9	330
VSTIM480	250	M48 x 2.0	54.8	21.5	27.5	17	44.6 x 2.9	420
VSTIM600	250	M60 x 2.0	64.8	24.0	30.0	19	56.6 x 2.9	500

* Not included in ISO 6149-4 standard